

Digital Servo DS-10

EQ OPTIMIZED BASS OUTPUT SUBWOOFER

Features

- Small cabinet
- LED front panel display
- One button Self-EQ
- Customizable listening presets
- Night-mode
- Advanced Auto-EQ and Manual-EQ



SPECIFICATIONS

MODEL	DS-10
Woofer	10" (24.5 cm) forward firing (8.0" piston diameter)
Amplifier: Class D	3000 watts Dynamic/ 1250 watts RMS Power
THD	<1% (typical)
Frequency Response	18 - 120 Hz +/- 3dB
High-Pass Crossover	80 Hz* @ 6 dB/octave
Low-Pass Crossover	15 - 199 Hz selectable slopes 1 Hz increments Default: 80 Hz @ 24 dB octave
Subsonic Filter	15 - 35 Hz selectable slopes 1 Hz increments Default: 15 Hz @ 24 dB octave
Polarity	Adjustable (+/-)
Digital Phase	0 - 180 degrees 15 degree increments
Magnet Structure	310 oz. (19.3 lbs)
Voice Coil	Tandem 3-inch push-pull
Cone	Kevlar-reinforced resin
LFE (Mono)	Line Level (RCA) Nominal Impedance 47K Balanced (XLR) Nominal Impedance 10K
Input (L&R)	Line Level (RCA)
Microphone	Balanced (mini XLR, cable included)
Speaker Level (L&R)	Bare wire, banana plugs, or spade lugs
Thru (L&R)	Line Level (RCA)
Output (L&R)	Line Level (RCA)
EQ Output	Line Level (RCA) for Test Signal (L/R) and Video (cables included)
Accessories	Remote control, Digital Drive Accessory Kit
Cabinet (HxWxD) (includes feet and grille)	11.75" x 11.75" x 13.5" (30 cm x 30 cm x 34 cm)
Warranty (parts/labor) (North America)	Three years (electronics) Five years (drivers)
Shipping Weight (approx.)	57 lbs. (26 Kg)

*Note: Varying speaker and amplifier input load impedances may cause the high-pass crossover frequency to slightly vary.