DD-18+

THE NEW INDUSTRY BENCHMARK IN LOW DISTORTION BASS

Features

- ***One-Touch Auto-EQ+ automates the seamless blend of subwoofer, system and room***
- ***Use your PC for manual adjustments and real time feedback of your bass performance***
- ***The industry's lowest distortion bass - under .5%***
- ***Sophisticated cone design for fast, accurate motion***
- ***Six-layer, custom wound voice coil assures better heat dissipation***
- ***Massive motor structure for amazing low-frequency energy***





SPECIFICATIONS

MODEL	DD-18+
Driver	18" forward firing
Amplifier Class D	3000 watts Dynamic 1250 watts RMS Power
Frequency Response Overall (+/- 3 dB)	 8.8 - 300 Hz 14.4 - 120 Hz
THD	<0.5% (typical)
High Pass Crossover	80 or 100 Hz at 6 dB/octave
Low Pass Crossover	40 Hz to 199 Hz (variable in 1 Hz increments) selectable slope Default: 80 Hz @ 24 dB/Octave
Phase	0 to 180 degrees (variable in 15 degree increments)
Polarity	Adjustable (+/-)
Magnet Structure	39.7 lbs.
Voice Coil	Six-layer, 75mm
Cone	Fiberglass Rohacell Laminate
INPUTS LFE (Mono)	 Line level (RCA), Nominal Impedance 47K, Balanced (XLR), Nominal Impedance 10K
Input (L&R)	Line level (RCA & XLR)
Microphone	Balanced (Mini-XLR, cable included)
Speaker Level (L&R)	Bare wire, banana plugs, or spade lugs
OUTPUTS Thru (L&R)	 Line level (RCA & XLR)
Output (L&R), High-Pass	Line level (RCA & XLR)
Included Accessories	Full feature remote control, DD+ accessory kit and video cable
Finishes	Black gloss ebony, satin cherry or walnut
Dimensions (H/W/D) (includes feet and connectors)	22.7" x 20.7" x 25.6" (58 x 53 x 65 cm)
Shipping Weight (approx)	142 lbs.